

Safety Data Sheet**SECTION 1: IDENTIFICATION****1.1. Product Identifier****Product Form:** Mixture**Product Name:** PURAMAX Antifreeze Concentrate**Product Grades/Codes:**

PURAMAX Green AF – 1911617110 (Bulk), 1911617121 (Tote), 1911617132 (Drum), 1911617160 (6X1G Case)

PURAMAX Gold Universal AF – 1911617010 (Bulk), 1911617021 (Tote), 1911617032 (Drum), 1911617060 (6X1G Case)

PURAMAX Red ELC AF – 1911617210 (Bulk), 1911617221 (Tote), 1911617232 (Drum), 1911617260 (6X1G Case)

Synonyms: Engine Antifreeze Coolant**1.2. Intended Use of the Product**

Engine Antifreeze Coolant

1.3. Company Identification

North American Lubricants Company

7337 E. Doubletree Ranch Road, Suite 180

Scottsdale, AZ 85258

(800)430-6252

www.nalube.com**1.4. Emergency Telephone Number****Emergency Number** : CHEMTREC: (800)424-9300 or (703)527-3887**SECTION 2: HAZARDS IDENTIFICATION****2.1. Classification of the Substance or Mixture****Classification (GHS-US)**

Acute Oral Tox, 4

Full text of H-phrases: see section 16

2.2. Label Elements**GHS-US Labeling****Hazard Pictograms (GHS-US)** :**Signal Word (GHS-US)** :

: Warning

Hazard Statements (GHS-US) :

: H302 Harmful if Swallowed

Precautionary Statements (GHS-US) :**Prevention**

P264 – Wash face, hands, and any exposed skin thoroughly after handling.

P270 – Do not eat, drink, or smoke when using this product.

Response

P301 +P312 – IF SWALLOWED: Call a poison center if you feel unwell.

P330 – Rinse Mouth

Disposal

P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

Safety Data Sheet

SDS# 2010, Version 1.0

Effective Date 6/1/2015

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

2.3. Other Hazards

None Known

2.4. Unknown Acute Toxicity (GHS-US)

none of the mixture consists of ingredient(s) of unknown acute toxicity.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Not applicable

3.2. Mixture

| Name | Product Identifier | % (w/w) | Classification (GHS-US) |
|------------------------------|--------------------|----------|-------------------------|
| Ethylene Glycol | (CAS No) 107-21-1 | 92 - 100 | H302, Acute Oral Cat 4 |
| Proprietary Additive Mixture | (CAS No) None | 0 - 8 | Not Classified |

*The specific chemical identity and/or exact percentage of composition have been withheld as a trade secret within the meaning of the OSHA Hazard Communication Standard [29 CFR 1910.1200].

*More than one of the ranges of concentration prescribed by Controlled Products Regulations has been used where necessary, due to varying composition.

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible).**Inhalation:** Remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.**Skin Contact:** Remove contaminated clothing. Drench affected area with water or soap and water for at least 15 minutes. Wash contaminated clothing before reuse. Obtain medical attention if irritation develops or persists.**Eye Contact:** Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.**Ingestion:** Do NOT induce vomiting. Rinse mouth. Call a POISON CENTER or doctor/physician if you feel unwell.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

General: No known significant effects or critical hazards.**Inhalation:** Overexposure may be irritating to the respiratory system.**Skin Contact:** Repeated or prolonged skin contact may cause irritation.**Eye Contact:** Direct contact with the eyes is likely irritating.**Ingestion:** Ingestion is likely to be harmful or have adverse effects.**Chronic Symptoms:** No known significant effects or critical hazards.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If you feel unwell, seek medical advice (show the label where possible).

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not flammable but will support combustion.

Explosion Hazard: Product is not explosive.

Reactivity: Hazardous reactions will not occur under normal conditions.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire. Under fire conditions, hazardous fumes will be present.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Under fire conditions, may produce fumes, smoke, oxides of carbon and hydrocarbons.

Other Information: Refer to Section 9 for flammability properties.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid all contact with skin, eyes, or clothing. Avoid breathing (vapor, mist, spray).

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Stop leak if safe to do so. Eliminate ignition sources. Ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Spills should be contained with mechanical barriers. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Heading 8. Exposure controls and personal protection. For further information refer to section 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: Any proposed use of this product in elevated-temperature processes should be thoroughly evaluated to assure that safe operating conditions are established and maintained. Practice good housekeeping - spillage can be slippery on smooth surface either wet or dry.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Materials: Strong acids, strong bases, strong oxidizers.

7.3. Specific End Use(s)

Engine Antifreeze Coolant

Safety Data Sheet

SDS# 2010, Version 1.0

Effective Date 6/1/2015

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government.

Ethylene Glycol (CAS No) 107-21-1 ACGIH TVL Ceiling 100mg/m³
OSHA PEL Ceiling 50 ppm
OSHA PEL Ceiling 125 mg/m³

8.2. Exposure Controls

Appropriate Engineering Controls: Ensure adequate ventilation, especially in confined areas. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national/local regulations are observed.

Personal Protective Equipment: Protective goggles. Gloves.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical goggles or safety glasses.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.

Environmental Exposure Controls: Do not allow the product to be released into the environment.

Consumer Exposure Controls: Do not eat, drink or smoke during use.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

| | |
|---------------------------|-----------------------|
| Physical State | : Liquid |
| Appearance | : Clear; may be dyed |
| Odor | : Characteristic |
| Odor Threshold | : Not available |
| pH | : Not available |
| Evaporation Rate | : Not available |
| Melting Point | : Not available |
| Boiling Point | : 100°C/212°F |
| Flash Point | : Typical 130°C/266°F |
| Auto-ignition Temperature | : 200°C/392°F |
| Decomposition Temperature | : Not available |
| Flammability (solid, gas) | : Not available |
| Lower Flammable Limit | : Not available |
| Upper Flammable Limit | : Not available |
| Vapor Pressure | : Not available |

Safety Data Sheet

SDS# 2010, Version 1.0

Effective Date 6/1/2015

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

| | |
|---|--|
| Relative Vapor Density at 20 °C | : Not available |
| Relative Density | : Not available |
| Specific Gravity | : Typical 1.1 at 15°C/59°F |
| Solubility | : Completely Soluble |
| Partition Coefficient: N-Octanol/Water | : Not available |
| Viscosity | : Not available |
| Viscosity, Kinematic | : Not available |
| Explosive Properties | : Product is not explosive |
| Explosion Data – Sensitivity to Mechanical Impact | : Not expected to present an explosion hazard due to mechanical impact |
| Explosion Data – Sensitivity to Static Discharge | : Not expected to present an explosion hazard due to static discharge |

SECTION 10: STABILITY AND REACTIVITY

- 10.1. **Reactivity:** Hazardous reactions will not occur under normal conditions.
- 10.2. **Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).
- 10.3. **Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4. **Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible materials, and other ignition sources.
- 10.5. **Incompatible Materials:** Strong acids, strong bases, strong oxidizers.
- 10.6. **Hazardous Decomposition Products:** No decomposition expected under normal use and storage conditions.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects - Product

Acute Toxicity: Not classified**LD50 and LC50 Data:** Not Classified**Skin Corrosion/Irritation:** Not classified**Eye Damage/Irritation:** Not classified**Respiratory or Skin Sensitization:** Not classified**Germ Cell Mutagenicity:** Not classified**Teratogenicity:** Not classified**Carcinogenicity:** Not classified**Specific Target Organ Toxicity (Repeated Exposure):** Not classified**Reproductive Toxicity:** Not classified**Specific Target Organ Toxicity (Single Exposure):** Not classified**Aspiration Hazard:** Not classified**Symptoms/Injuries After Inhalation:** Overexposure may be irritating to the respiratory system.**Symptoms/Injuries After Skin Contact:** Repeated or prolonged skin contact may cause irritation.**Symptoms/Injuries After Eye Contact:** Direct contact with the eyes is likely irritating.**Symptoms/Injuries After Ingestion:** Ingestion is likely to be harmful or have adverse gastrointestinal effects.**Chronic Symptoms:** Not Classified

11.2. Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Ethylene Glycol

LD50 Oral Rat 4000 mg/kg

LD50 Dermal Rabbit 9530 ul/kg

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General:

Safety Data Sheet

SDS# 2010, Version 1.0
Effective Date 6/1/2015

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Ethylene Glycol**Algae**

EC50 96 hr. 6500- 13000mg/l (Pseudokirchneriella subcapitata)

Fish

LC50 96 hr. 14 – 18 mL/L (Oncorhynchus mykiss)

LC50 96 h: 40000 - 60000 mg/L static (Pimephales promelas)

LC50 96 h: = 16000 mg/L static (Poecilia reticulata)

LC50 96 h: = 27540 mg/L static (Lepomis macrochirus)

LC50 96 h: = 40761 mg/L static (Oncorhynchus mykiss)

LC50 96 h: = 41000 mg/L (Oncorhynchus mykiss)

Microorganisms

EC50 = 10000 mg/L 16 h

EC50 = 620 mg/L 30 min

EC50 = 620.0 mg/L 30 min

Daphnia Magna (Water Flea)

EC50 48 h: = 46300 mg/L (Daphnia magna)

12.2. Persistence and Degradability

Not available

12.3. Bioaccumulative Potential

Not available

12.4. Mobility in Soil

Not available

12.5. Other Adverse Effects**Other Information:** Avoid release to the environment.**SECTION 13: DISPOSAL CONSIDERATIONS****13.1. Waste treatment methods****Sewage Disposal Recommendations:** Do not empty into drains; dispose of this material and its container in a safe way. Do not empty into drains. Do not dispose of waste into sewer.**Waste Disposal Recommendations:** Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.**SECTION 14: TRANSPORT INFORMATION****14.1. In Accordance with DOT****UN Number -** UN3082**Proper Shipping Name -** Environmentally hazardous substances, liquid, n.o.s.**Hazard Class** 9**Packing Group** III**Reportable Quantity (RQ)** Ethylene glycol: RQ kg=9080**DOT Packaging Exceptions** 155**DOT Packaging Non Bulk** 203**Other Information** Non Bulk is not regulated by the US DOT (in quantities under 5,000 lbs in any one inner package.)**14.2. In Accordance with IMDG** Not regulated for transport**14.3. In Accordance with IATA** Not regulated for transport**14.4. In Accordance with TDG** Not regulated for transport

Safety Data Sheet

 SDS# 2010, Version 1.0
 Effective Date 6/1/2015

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

SECTION 15: REGULATORY INFORMATION
15.1. US Federal Regulations

| | |
|---------------------------------------|--|
| SARA Section 311/312 Hazard Classes | Acute Health Hazard |
| SARA Section 313 – Threshold Value 1% | Ethylene glycol, 107-21-1, wt% 50 - 58 |
| CERCLA – RQ, 5,000 lbs | Ethylene glycol |

15.2. US State Regulations

California - Prop 65 – This product does not contain any Proposition 65 Chemicals.

Illinois – Right to Know – Ethylene glycol

Massachusetts – Right to Know - Ethylene glycol

New Jersey – Right to Know – Ethylene glycol

Pennsylvania – Right to Know – Ethylene glycol

Rhode Island – Right to Know – Ethylene glycol

15.3. Canadian Regulations

| | |
|----------------------|----------------|
| WHMIS Classification | Not Classified |
|----------------------|----------------|

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date : 06/25/2015
Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

| | |
|-------------|--|
| H302 | Harmful if Swallowed |
| P264 | Wash face, hands, and any exposed skin thoroughly after handling. |
| P270 | Do not eat, drink, or smoke when using this product. |
| P301 + P312 | IF SWALLOWED: Call a poison center if you feel unwell. |
| P330 | Rinse Mouth |
| P501 | Dispose of contents/container in accordance with local, regional, national, and international regulations. |

Party Responsible for the Preparation of This Document

North American Lubricants Company
 7337 E. Doubletree Ranch Road, Suite 180
 Scottsdale, AZ 85258
 (800)430-6252
www.nalube.com

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.