



PureGreen Supreme Motor Oil

PureGreen® Supreme Motor Oil is a synthetic blend engine oil designed to provide superior performance in both passenger cars and light duty trucks. Formulated from premium quality re-refined base stocks, it offers the unique combination of optimum lubricant performance and environmental conservation.

PureGreen Supreme Motor Oil is available in SAE grades 5W-20, 5W-30, and 10W-30 and meets new car warranty requirements as defined by ILSAC standards GF-6A and API classification Resource Conserving SP.

APPLICATIONS

For gasoline-fueled and flex-fuel passenger cars, light trucks, and sport utility vehicles.

FEATURES AND BENEFITS

- Conserves irreplaceable petroleum resources
- Reduces U.S. reliance on foreign crude oil
- Helps protect against low speed pre-ignition (LSPI) in turbocharged gasoline direct injection engines (TGDI)
- Long-lasting fuel economy performance
- Unsurpassed engine protection
- Excellent low-temperature performance
- Advanced high-temperature performance
- Meets the latest ILSAC GF-6A and API Resource Conserving SP categories
- Made from the finest quality base stocks and robust additive technologies
- Flex-fuel (up to 85% ethanol) capable

RECOMMENDED PERFORMANCE SPECIFICATIONS

- ILSAC GF-6A / API Resource Conserving SP and all previous “S” categories
- FCA Chrysler MS-6395 (Revision S)
- Ford WSS-M2C960-A1 (SAE 5W-20), WSS-M2C961-A1 (SAE 5W-30)
- GM6094M (Obsolete)

PureGreen Supreme Motor Oil	Test Method	Typical Characteristics		
		SAE Viscosity Grade		
		5W-20	5W-30	10W-30
Gravity, °API	1298	32.5	32.5	31.8
Flash Point, COC °C/°F	92	215/420	215/420	220/430
Pour Point, °C/°F	97	-34/-30	-34/-30	-32/-20
Viscosity				
cSt @ 40°C	445	49.0	62.7	69.6
cSt @ 100°C	445	8.5	10.8	10.6
Viscosity Index	2270	152	161	142
CCS Viscosity (mPa.s)	5298	<6600@-30	<6600@-30	<7000@-25
Noack Volatility (%wt)	5800	<15	<15	<15

Minor variations in test data are to be expected in normal manufacturing