



Puratech Sure-Shift ATF

Puratech Sure-Shift ATF is designed and recommended for automatic transmissions that require General Motors DEXRON®-III or Ford MERCON® fluids.

Puratech Sure-Shift ATF's state-of-the-art additive system exceeds both current and previous generation performance specifications of DEXRON® and MERCON® fluids.

APPLICATIONS

Puratech Sure-Shift ATF may also be used in equipment requiring a "Type A" ATF fluid, Allison C-4, Caterpillar TO-2, and Ford specifications M2C138-CJ and M2C166-H.

Puratech Sure-Shift ATF also makes an excellent hydraulic fluid in mobile or industrial applications where low temperature fluidity or leak detection is an important consideration.

FEATRURES AND BENEFITS

- Superior wear protection
- Excellent frictional properties for smooth shifting
- Excellent anti-shudder performance
- Protection against varnish and sludge formation
- Superior thermal stability and oxidation resistance
- Outstanding low-temperature

Puratech Sure-Shift ATF	Typical Characteristics
Density, g/cm ³ @ 15 °C	.860
Flash Point, COC C° (F°)	212 (413)
Viscosity, cP @ -20 °C	1300
Viscosity, cP @ -30 °C	4200
Viscosity, cP @ -40 °C	17000
Viscosity, cP @ 40 °C	35.4
Viscosity, cSt @ 100 °C	7.2
Viscosity Index	172
Pour Point, C° (F°)	-52 (-61)
Color	Red
Foam Test, ASTM D892	Pass