

**INTRODUCING**

# **PRIME**<sup>®</sup>

**BY Prestone**



### **Prime<sup>®</sup> Orange Compatible**

**CONCENTRATE EXTENDED LIFE**  
**UP TO 5 YEARS / 150,000 MILES\***

PRODUCT	AF3400
ITEM UPC	7 97496-87902 8
DRUM	AF3455
TOTE	-
BULK	-
CASE UPC	7 97496-87904 2

### **Prime<sup>®</sup> Orange Compatible**

**50/50 PREDILUTED EXTENDED LIFE**  
**UP TO 5 YEARS / 150,000 MILES\***

PRODUCT	AF3500 / P-4975
ITEM UPC	7 97496-87903 5
DRUM	AF3555 / P-0000
TOTE	-
BULK	-
CASE UPC	7 97496-87905 9

# PRIME<sup>®</sup>

BY Prestone

## CONCENTRATE EXTENDED LIFE

### GENERAL DESCRIPTION

Composition by Weight	Typical Values	
Inhibited Glycols:	97.9%	
Total Water:	2.1%	
Dyes:	Trace	

  

Properties	Typical Values	Tests
Color:	Orange	
Odor:	Characteristic	
Ash Content:	1.09%	ASTM D1119
pH: (50% by Vol. Solution)	8.7	ASTM D1287
Reserve Alkalinity:	5.15	ASTM D1121
Specific Gravity at 20/20°C: (50% by Vol. Solution)	1.0709	ASTM D1122
Freezing Point (50% by Vol. Solution):	-34°F	ASTM D1177
Boiling Point**: (50% by Vol. Solution)	+226°F	ASTM D1120
Foam Test:	50 ml max, 1.0 sec. max break time	ASTM D1881

\*\*Under standard pressure

## 50/50 PREDILUTED EXTENDED LIFE

### GENERAL DESCRIPTION

Composition by Weight	Typical Values	
Antifreeze/Coolant Concentrate:	51.0%	
Total Water:	49.0%	
Dyes:	Trace	

  

Properties	Typical Values	Tests
Color:	Orange	
Odor:	Characteristic	
Ash Content:	0.54%	ASTM D1119
pH:	8.7	ASTM D1287
Reserve Alkalinity:	2.6	ASTM D1121
Specific Gravity at 20/20°C:	1.0709	ASTM D1122
Freezing Point:	-34°F	ASTM D1177
Boiling Point**:	+226°F	ASTM D1120
Foam Test:	50 ml max, 1.0 sec. max break time	ASTM D1881

\*\*Under standard pressure

PROTECTION	FREEZE-UP PROTECTION	BOIL-OVER PROTECTION†	CORROSION PROTECTION
<b>MINIMUM</b> 50% Antifreeze 50% Water	<b>-34°F</b>	<b>+265°F</b>	Meets or exceeds ASTM D3306 ASTM D4985
<b>MAXIMUM</b> 70% Antifreeze 30% Water	<b>-84°F</b>	<b>+276°F</b>	

† Using a 15 lb. pressure cap in good condition

PROTECTION	FREEZE-UP PROTECTION	BOIL-OVER PROTECTION†	CORROSION PROTECTION
50/50 PREDILUTED Antifreeze/Coolant	<b>-34°F</b>	<b>+265°F</b>	Meets or exceeds ASTM D3306 ASTM D4985

† Using a 15 lb. pressure cap in good condition

UPC Item



UPC Case



50/50 - UPC Item



50/50 - UPC Case



Case Pack:	Case Size (in.):	Case Weight (lb.):	Case Cube (cu ft.):	Pallet Load Size (in.):	Cases Per Tier:	Tiers Per Pallet:	Cases Per Pallet:	Load Weight (lb.):
6	L 15.75 x W 12.94 x H 12.19	60	1.437721615	L 47.25 x W 38.81 x H 48.75	9	4	36	2150

\* Provides extended life protection for up to 5 years or 150,000 miles when flushed and filled according to manufacturer's recommendations.