



ALL-PURPOSE GREASE NLGI #2

CITADEL All-Purpose Grease is ideal for general purpose lubrication for use in automotive, light industrial and commercial applications calling for a lithium grease. Engineered to provide water resistance and corrosion protection. CITADEL All-Purpose Grease utilizes a lithium 12-hydroxystearate thickener compatible with most lithium and lithium complex greases.



APPLICATIONS:

Ideal for use in applications calling for a lithium grease where general purpose lubrication is needed.

- Automotive chassis lubrication
- Ball joints
- Universal joints
- General agriculture applications
- Light industrial lubrication
- 5th wheel protection
- Non-disk brake wheel bearings
**Not recommended for disk brake wheel bearings*

FEATURES & BENEFITS:

- Excellent low temperature pumpability
- Water resistance & washout
- Rust & corrosion protection
- Oxidation resistance

RECOMMENDED PERFORMANCE SPECIFICATIONS:

CITADEL All-Purpose Grease is compatible with other greases that use a lithium-based thickener. Always consult a grease compatibility chart to determine whether it is acceptable to mix with other thickener types.

- NLGI Grade 2

CITADEL All-Purpose Grease		Typical Characteristics
NLGI	Test Method ASTM -D	2
Penetration, mm/10		
Worked 60 strokes	217	265-295
Dropping Point, °C (°F)	2265	188(370)
Thickener Type		Lithium 12-HSA
Color	Visual	Amber
Base Oil Viscosity, Kinematic	445	ISO 150
Oxidation Stability, lb loss/100 hrs	942	5
Bearing rust protection	1743	Pass
Water Spray-off, %	4049	28

Minor variations in test data are to be expected in normal manufacturing