



ANYWHERE. ANYTIME. ANY ENGINE.™

## Heavy Duty 2 in 1 Flush & Degreaser



**Available Now!**

Introducing Prestone's New Command 2in1 Flush & Degreaser for heavy duty diesel cooling systems. Innovative and easy to use, Command 2in1 Flush & Degreaser reduces downtime by cleaning and degreasing in one step.

**Part 1** is an advanced cleaner that safely dissolves corrosion and scale without damaging metals, or disassembling the cooling system.

**Part 2** is an oil encapsulation system that strips grease and oil from all surfaces and flushes it away. Just one use helps prevent overheating, a major cause of engine failure.

### FEATURES & BENEFITS

#### PERFORMANCE

- Eliminate oil & fuel contamination
- Strip away corrosion by product from metal surfaces
- Remove aluminum corrosion, silicate gel, and rust
- Restores cabin heat
- Fast and easy to use

#### SAFE FOR ALL

- HD coolants
- Metals
- Gaskets
- Hoses
- Plastics
- HD trucks, vans, buses and off-road equipment



ANYWHERE. ANYTIME. ANY ENGINE.™

### HEAVY DUTY 2 IN 1 FLUSH & DEGREASER

#### PRODUCT INFORMATION

Stock #:	HD100
SDS #:	745
UPC Item:	7 97496-88017 8
UPC Case:	7 97496-88018 5
Product Size (in.):	<b>L</b> 7.5 x <b>W</b> 3.8 x <b>H</b> 11.8
Case Pack:	6/1 Gallon Plastic Bottles
Case Size (in.):	<b>L</b> 15.75 x <b>W</b> 13.25 x <b>H</b> 12.56
Case Weight (lb.):	57.2
Case Cube (cu ft.):	0.2033
I2 of 5:	10797496880175
Pallet Load Size (in.):	<b>L</b> 48 x <b>W</b> 40 x <b>H</b> 48.75
Cases Per Tier:	9
Tiers Per Pallet:	4
Cases Per Pallet:	36
Load Weight (lb.):	2100

#### APPLICATION

- 1) Drain the cooling system, add 2 in 1 Flush & Degreaser and refill with water. (systems larger than 16 gallons require second bottle)
- 2) Bring the engine up to operating temperature and ensure circulation through the entire cooling system for at least 45 minutes. Systems that are especially dirty or oily can be run for up to 3 hours.
- 3) Thoroughly flush the cooling system with water.
- 4) Drain the cooling system, replace coolant filter if equipped, and install half of the cooling system capacity with Prestone Command Concentrate Antifreeze/Coolant. Top off with water and thoroughly mix by driving.
- 5) Verify the coolant concentration and level and top off as necessary.

#### HANDLING

Do not reuse container. Keep container closed. Dispose of according to federal, state, or local regulations.

#### ADDITIONAL PRODUCTS



Scan here! To see what's **NEW** at Prestone®