



PURAMAX Concrete Form Oil

PURAMAX Concrete Form Oil is a light colored mineral oil designed to provide clean and easy separation of concrete from wood and metal forms. Its non-staining characteristics make it ideal for applications that require exceptional surface finish.

APPLICATIONS

- Designed for clean and easy separation of concrete from wood and metal forms
- Sprayed on cement mixer drums to facilitate clean-up of cement mixers
- Specialty concrete products requiring excellent surface finish

FEATURES AND BENEFITS

- Easily applied by brush, mop, roller or sprayer
- Non-staining, will not discolor concrete
- Allows for easy removal of forms
- Excellent surface finish
- Low viscosity and pour point allows for year round use
- Extends form life by protecting wood and preventing rust on metal
- Meets EPA AIM and OTC phase 1 VOC requirements

SPECIAL HANDLING, NOTICES OR WARNINGS

Handle as you would any petroleum product.

| PURAMAX Concrete Form Oil | | Typical Characteristics |
|----------------------------------|----------------------------|--------------------------------|
| | <i>Test Method ASTM -D</i> | |
| API Gravity | 1298 | 33 |
| Flash Point, °C/°F | 92 | 149/300 |
| Pour Point, °C/°F | 97 | -40/-40 |
| Viscosity | | |
| cSt @ 40 °C | 445 | 17 |
| cSt @ 100 °C | 445 | 4 |

Minor variations in test data are to be expected in normal manufacturing