

PURAMAX Universal Tractor Fluid

PURAMAX Universal Tractor Fluid is formulated from premium base stocks and state-of-the-art additive technology. It is designed for use in a variety of farm equipment, off-highway machinery, industrial tractors, final drives, power take-off units, wet brakes, power steering units and hydraulic systems.

PURAMAX Universal Tractor Fluid is made with special friction modifiers combined with extremely shear-stabile viscosity modifiers offer a supreme performance level. This new and improved fluid offers the convenience of using one tractor fluid in place of two or more fluids while maintaining optimum component performance and durability.

APPLICATIONS

PURAMAX Universal Tractor Fluid is suitable for use in all major OEM equipment including but not limited to Kubota, Oliver, Minneapolis-Moline, International Harvester, White Farm, John Deere, Deutz-Allis Chalmers, Ford-New Holland, J.I. Case and Massey Ferguson.

PURAMAX Universal Tractor Fluid is suitable for use where the following specifications are recommended:

- John Deere- Quatrol, J20A, J20C, J21A, Hy-Gard J14B/C, Type 303
- International Harvestor- Hy-Tran, B-6
- Massey Ferguson- M-1110, M-1127B, M-1129A, M-1135, M-1141
- Allis Chalmers- Power Fluid 821 XL
- J.I. Case- TFD (JIC-143/146), Hi-Vis (JIC-185), JIC-144/145, MS-1204, MS1205/1206/1207, MS-1210 (TCH) and B-6
- Ford New Holland- M2C86-A/B/C, M2C134-A/B/C/D, M2C41-B, M2C43, M2C53-A/B, M2C92-A
- Vickers- I-2986-S
- Kubota Universal Transdraulic Fluid- UTD

FEATRURES AND BENEFITS

- Superior wear protection
- Excellent rust and corrosion protection
- Protection against varnish and sludge formation
- Superior thermal stability and oxidation resistance
- Outstanding low-temperature

PURAMAX Universal Tractor Fluid	Typical Characteristics
Specific Gravity	0.86
Lbs. / gallon	7.2
Viscosity, cPs @ 100 ℃	9.6
Viscosity, cPs @ 40 ℃	54.4
Viscosity Index	119
Flash Point, C°	218
Pour Point, C°	-35