

Safety Data Sheet**SECTION 1: IDENTIFICATION****1.1. Product Identifier****Product Form:** Mixture**Product Name:** PURAMAX GEO MMCC SAE 40 LA**Product Grades/Codes:**

PURAMAX GEO MMCC SAE 40 LA – 2111362818 (320G Tote)

1.2. Intended Use of the Product

Gas Engine Oil

1.3. Company IdentificationNorth American Lubricants Company
7337 E. Doubletree Ranch Road, Suite 180
Scottsdale, AZ 85258
(800) 430-6252
www.nalube.com**1.4. Emergency Telephone Number****Emergency Number** : CHEMTREC: (800) 424-9300 or (703) 527-3887**SECTION 2: HAZARDS IDENTIFICATION****2.1. OSHA/HCS Status:**

This material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

2.2. Classification(s):

Not Classified

2.3. Signal Word:

No Signal Word

2.4. Symbol(s):

No Symbol

2.5. Hazard Statement(s):

No known significant effects or critical hazards.

2.6. Precautionary Statement(s):

No precautionary phrases.

Hazard Rating

	HMIS
Health:	1
Flammability:	1
Reactivity:	0
Special	B

Safety Data Sheet

2.7. General Precautionary Statement(s):

Keep out of reach of children.

Read label before use.

Wash skin thoroughly after handling.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention if you feel unwell.

2.8. Prevention Precautionary Statement(s):

Not Applicable

2.9. Response Precautionary Statement(s):

Not Applicable

2.10. Storage Precautionary Statement(s):

Store in a dry place.

Store in a closed container.

2.11. Disposal Precautionary Statement(s):

Dispose of contents/containers should be cleaned of residual product before disposal, and disposed of in accordance with all applicable laws and regulations.

2.12. Other Hazards Which Do Not Result in Classification:

No additional information available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Component Listing:

Ingredient Name	Amount	CAS Number
Highly Refined Petroleum Base Oil	85-95	Mixture
Additives	<20	Proprietary

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

SECTION 4: FIRST AID MEASURES

4.1. Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible).

Eye Contact: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Skin Contact: Wash skin with plenty of soap and water while removing contaminated clothing and shoes.

Inhalation: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Ingestion: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

Notes to Physician: Treat symptomatically.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

4.2. Most Important Symptoms and Effects Both Acute and Delayed

General: No known significant effects or critical hazards.

Inhalation: Overexposure may be irritating to the respiratory system.

Skin Contact: Repeated or prolonged skin contact may cause irritation.

Eye Contact: Direct contact with the eyes is likely irritating.

Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: No known significant effects or critical hazards.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If you feel unwell, seek medical advice (show the label where possible).

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Carbon dioxide, foam, or dry powder. Do not use water, because this product is oil based. Water may cause frothing.

5.2. Flammable Properties

COC Flash Point: 258°C (498 °F)

Autoignition Temperature: N/A

5.3. Flammable Properties

COC Flash Point: 258 °C (498 °F)

Autoignition Temperature: N/A

5.4. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire. Under fire conditions, hazardous fumes will be present.

Firefighting Instructions: Use water fog, foam, dry chemical or CO₂. Do not use water, because this product is oil based. Water or Foam may cause frothing.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Under fire conditions, may produce fumes, smoke, oxides of carbon and hydrocarbons.

Other Information: Refer to Section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid all contact with skin, eyes, or clothing. Avoid breathing (vapor, mist, spray).

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

Safeguards: Eliminate all sources of ignition – heat, sparks, flame, electricity, impact and friction.

Safety Data Sheet

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Stop leak if safe to do so. Eliminate ignition sources. Ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and Material for Containment and Cleaning Up

Safeguards (Personnel): Eliminate all sources of ignition – heat, sparks, flame, electricity, impact and friction.

Initial Containment: Absorb spills with inert material. Do not allow material to enter soil or surface water.

Large Spills Procedure: Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Do no flush to sewer.

Small Spills Procedure: Absorb spills with inert material.

Miscellaneous: Treat or dispose of in accordance with all federal, state, and local requirements. Incineration is preferred.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Handling (Personnel): Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition; they may explode and cause injury or death.

Empty drums should be completely drained, properly bunged, and promptly returned to a drum reconditioner, or properly disposed of. Wash hands thoroughly after handling.

Handling (Physical Aspects): Secure container after each use. Store in a cool, dry area. Avoid contact with strong oxidizing agents.

Additional Hazards When Processed: Any proposed use of this product in elevated-temperature processes should be thoroughly evaluated to assure that safe operating conditions are established and maintained. Practice good housekeeping - spillage can be slippery on smooth surface either wet or dry.

Pre-existing Conditions: Pre-existing skin and respiratory disorders may be aggravated by exposure to this product. The International Agency for Cancer Research has determined there is sufficient evidence for the carcinogenicity in experimental animals exposed by contact to used motor (crankcase) oil. Handling procedures and safety precautions in the MSDS should be followed to minimize exposure to the product as used lubricating oil in gasoline or diesel fueled internal combustion engines.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Storage Precautions: Store in a cool dry place, in a tightly closed container. Eliminate all sources of ignition – heat, sparks, flame, electricity, impact, and friction.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Safety Data Sheet

 SDS# 5093, Version 1.0
 Effective Date 5/28/2021

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Occupational Exposure Limits

MATERIAL	SOURCE	TYPE	mg/m ³
Oil Mist, Mineral	ACGIH	TWA (Inhalable fraction.)	5 mg/m ³
Oil Mist, Mineral	ACGIH	STEL (Mist.)	10 mg/m ³
Oil Mist, Mineral	OSHA	TWA (Mist.)	5 mg/m ³

Engineering Controls: Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product. TLV for mineral oil is 5 mg/cubic meter.

Eye / Face Protection Requirement: When splashing of the material may occur, chemical goggles and/or a face shield are recommended.

Skin Protection Requirements: Where contact is likely, wear chemical resistant gloves.

Respiratory Protection Requirements: Under normal use conditions, with adequate ventilation, no special handling equipment is required. If mists are produced, local ventilation may be required to keep exposure below limits.

Occupational Exposure Limits: Estimated 8-hour workday.

General Comments: Always observe good personal hygiene practices. Wash hands and other exposed skin areas with plenty of mild soap and water before eating, drinking, smoking, etc.

8.2. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government.

8.3. Exposure Controls

Appropriate Engineering Controls: Ensure adequate ventilation, especially in confined areas. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national/local regulations are observed.

Personal Protective Equipment: Protective goggles. Gloves. Insufficient ventilation: wear respiratory protection.

Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical goggles or safety glasses.

Skin and Body Protection: Wear suitable protective clothing.



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	Liquid
Color	Dark Amber
Odor	Petroleum

Safety Data SheetSDS# 5093, Version 1.0
Effective Date 5/28/2021

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Vapor Density	Heavier than air (Air = 1)
Solubility in Water	Nil
Specific Gravity	0.8740 at 60 °F (Water = 1)
Bulk Density	7.28 Pound per Gallon at 60 °F
Pour PT	-15 °C
pH	Not Applicable
Viscosity	12.9 cSt at 100 °C

SECTION 10: STABILITY AND REACTIVITY**10.1. Stability:** Stable**10.2 Hazardous Polymerization:** Will not occur**10.3 Incompatibility with Other Materials:** Avoid contact with strong oxidizing agents**10.4 Hazardous Decomposition Products:** In the case of a fire, oxides of carbon, hydrocarbons, fumes, and smoke may be produced. Hydrogen sulfide and alkyl mercaptans and sulfides may also be released.**SECTION 11: TOXICOLOGICAL INFORMATION****11.1. Information on Toxicological Effects****GENERAL INFORMATION:**

Based on data on the components and the toxicology of similar materials

ROUTES OF ENTRY:

Skin, Eyes, Ingestion, and Inhalation.

ACUTE EXPOSURE:

N/A

EYE IRRITATION:

Not expected to cause eye irritation. Based on data from components or similar materials.

Vapors may cause irritation.

SKIN IRRITATION:

Slightly irritating based on data from components or similar materials. Prolonged or repeated skin contact without proper hygiene may result in skin disorders such as acne.

RESPIRATORY IRRITATION:

Based on data from components and similar materials, Inhalation of vapors or mists may cause irritation.

DERMAL TOXICITY:

Expected to be of low toxicity: LD50 > 5000 mg/kg, Rabbit

ORAL TOXICITY:

Expected to be of low toxicity: LD50 > 5000 mg/kg, Rat

INHALATION TOXICITY:

Based on data from components and similar materials, product is not considered to be an inhalation hazard under normal conditions of use.

Safety Data Sheet

SDS# 5093, Version 1.0
Effective Date 5/28/2021

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

SENSITISATION:

Component concentrations in this formulation would not be expected to cause skin sensitization, based on tests of the components or similar formulations.

CHRONIC EXPOSURE:

N/A

CHRONIC TOXICITY:

No data available to indicate product or components present at greater than 1% are chronic health hazards.

CARCINOGENICITY:

Product contains mineral and/or synthetic oils shown to be noncarcinogenic in laboratory studies with the same or similar materials. Mineral and synthetic oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC). Other components are not known to be associated with carcinogenic effects.

MUTAGENICITY:

No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

REPRODUCTIVE TOXICITY:

No data available to indicate either product or components present at greater than 0.1% that may cause reproductive toxicity.

TERATOGENICITY:

No data available to indicate either product or components present at greater than 0.1% that may cause birth defects.

ADDITIONAL INFORMATION:

No other health hazards known.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Environmental Hazards:

This product is classified as an oil under section 311 of the Clean Water Act. Spills entering (A) surface waters or (B) any water courses or sewer's-entering/leading to surface waters that cause a sheen must be reported to the nearest local Environmental Protection Agency Office.

12.2 Environmental Fate

This material is not expected to be readily biodegradable. The biodegradability of this material is based on an evaluation of data for the components or a similar material. This product contains components which may be persistent in the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste Treatment Methods

Product is suitable for burning in an enclosed, controlled burner for fuel value or disposal by supervised incineration. Proper characterization is recommended. The product is suitable for processing by an approved recycling facility or can be disposed of at an appropriate government waste disposal facility. Compliance with all appropriate Federal, State, and Local regulations should be satisfied at time of disposal. Base Oil Component is expected to be inherently biodegradable. The total mixture may be harmful to aquatic organisms.

Safety Data SheetSDS# 5093, Version 1.0
Effective Date 5/28/2021

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

SECTION 14: TRANSPORT INFORMATION

- Product Label: RFT Premium Low Ash Natural Gas Engine Oil SAE 40.
D.O.T Shipping: Not Regulated by DOT.
IMDG: This material is not classified as dangerous under IMDG regulations.
IATA: This material is not classified as dangerous under IATA regulations.
Transport Canada: This material is not classified as dangerous under Transport Canada regulations.

SECTION 15: REGULATORY INFORMATION**15.1. Regulatory Lists Searched:**

- United States Inventory (TSCA): All components are listed or exempted.
Canada Inventory: All components are listed or exempted.
Europe Inventory: All components are listed or exempted.
Japan Inventory (ENCS): All components are listed or exempted.
Australia Inventory (AICS): All components are listed or exempted.
Korea Inventory (KECI): All components are listed or exempted.
China Inventory (IECSC): All components are listed or exempted.
Philippines Inventory (PICCS): All components are listed or exempted.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

- Revision Date** : 5/28/2021
Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

- P273: Avoid release into the environment
P501: Dispose of contents/container in accordance with local, regional, national, and international regulations.

Party Responsible for the Preparation of This Document

North American Lubricants Company
7337 E. Doubletree Ranch Road, Suite 180
Scottsdale, AZ 85258
(800)430-6252
www.nalube.com

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. North American Lubricants Company assumes no responsibility for injury from the use of the product described herein.