### **Safety Data Sheet**

### **SECTION 1: IDENTIFICATION**

1.1. Product Identifier
Product Form: Mixture
Product Name: PURAMAX CleanFleet Heavy Duty Engine Oil
Product Grades/Codes:
PURAMAX CleanFleet SAE 15W-40 CJ-4/SN- 1411191310 (Bulk), 1411191321 (Tote), 1411191330 (Drum), 1411191351 (Pail), 1411191351 (Pail), 1411191362 (3X1G Case)
PURAMAX CleanFleet SAE 10W-30 CJ-4/SN – 1011171310 (Bulk)

Synonyms: Engine Oil1.2. Intended Use of the ProductEngine Oil.

### 1.3. Company Identification

North American Lubricants Company 7337 E. Doubletree Ranch Road, Suite 180 Scottsdale, AZ 85258 (800)430-6252 www.nalube.com

### 1.4. Emergency Telephone Number

Emergency Number : CHEMTREC: (800)424-9300 or (703)527-3887

### SECTION 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the Substance or Mixture

Classification (GHS-US)

Not Classified

Full text of H-phrases: see section 16

### 2.2. Label Elements

GHS-US Labeling Hazard Pictograms (GHS-US)

None Required

Signal Word (GHS-US)	: Not Hazardous
Hazard Statements (GHS-US)	: None Required

# Precautionary Statements (GHS-US) : P273 - Avoid release to the environment. P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

### 2.3. Other Hazards

The mixture consists of substances capable of producing an aspiration hazard. Aspiration may result in chemical pneumonia (fluid

## line the second second

## Safety Data Sheet

in the lungs), severe lung damage, respiratory failure, and even death.

### 2.4. Unknown Acute Toxicity (GHS-US)

20.73 percent of the mixture consists of ingredient(s) of unknown acute toxicity.

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Substances

Not applicable

### 3.2. Mixture

Name	Product Identifier	% (w/w)	Classification (GHS-US)
Petroleum distillates, solvent dewaxed	(CAS No) 64742-65-0	75.75 – 95, 64 - 85	Not Classified
heavy paraffinic, Distillates, petroleum, hydrotreated heavy paraffinic	(CAS No) 64742-54-7	0 - 11, 10 - 17	Not Classified
Paraffin oils*	(CAS No) 8012-95-1	0 - 0.1, 0.1- 1, 1 - 5	Not Classified
Phenol, 4-dodecyl-	(CAS No) 104-43-8	0.1 - 1	Aquatic Chronic 3, H402
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	(CAS No) 68649-42-3	2.7 - 11.75	Aquatic Chronic 3, H402

\*The specific chemical identity and/or exact percentage of composition have been withheld as a trade secret within the meaning of the OSHA Hazard Communication Standard [29 CFR 1910.1200].

\*More than one of the ranges of concentration prescribed by Controlled Products Regulations has been used where necessary, due to varying composition.

Full text of H-phrases: see section 16

### **SECTION 4: FIRST AID MEASURES**

### 4.1. Description of First Aid Measures

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible). **Inhalation:** Remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.

**Skin Contact:** Remove contaminated clothing. Drench affected area with water or soap and water for at least 15 minutes. Wash contaminated clothing before reuse. Obtain medical attention if irritation develops or persists.

**Eye Contact:** Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

Ingestion: Do NOT induce vomiting. Rinse mouth. Immediately call a POISON CENTER or doctor/physician.

### 4.2. Most Important Symptoms and Effects Both Acute and Delayed

General: No known significant effects or critical hazards.

Inhalation: Overexposure may be irritating to the respiratory system.

Skin Contact: Repeated or prolonged skin contact may cause irritation.

Eye Contact: Direct contact with the eyes is likely irritating.

Ingestion: Ingestion is likely to be harmful or have adverse effects.

**Chronic Symptoms:** No known significant effects or critical hazards.

### 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

## line the second second

## Safety Data Sheet

If you feel unwell, seek medical advice (show the label where possible).

### SECTION 5: FIRE-FIGHTING MEASURES

### 5.1. Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

### 5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not flammable but will support combustion.

Explosion Hazard: Product is not explosive.

Reactivity: Hazardous reactions will not occur under normal conditions.

### 5.3. Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire. Under fire conditions, hazardous fumes will be present.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection. **Hazardous Combustion Products**: Under fire conditions, may produce fumes, smoke, oxides of carbon and hydrocarbons.

Other Information: Refer to Section 9 for flammability properties.

### **Reference to Other Sections**

Refer to section 9 for flammability properties.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid all contact with skin, eyes, or clothing. Avoid breathing (vapor, mist, spray).

### 6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

#### 6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

**Emergency Procedures:** Stop leak if safe to do so. Eliminate ignition sources. Ventilate area.

### 6.2. Environmental Precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and Material for Containment and Cleaning Up

**For Containment:** Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. **Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely. Spills should be contained with mechanical barriers. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

### 6.4. Reference to Other Sections

See Heading 8. Exposure controls and personal protection. For further information refer to section 13.

### SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for Safe Handling

Additional Hazards When Processed: Any proposed use of this product in elevated-temperature processes should be thoroughly evaluated to assure that safe operating conditions are established and maintained. Practice good housekeeping - spillage can be slippery on smooth surface either wet or dry.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

### 7.2. Conditions for Safe Storage, Including Any Incompatibilities

Date of Issue: 6/1/2015

### Safety Data Sheet

SDS# 5041, Version 1.0 Effective Date 6/1/2015 According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Technical Measures: Comply with applicable regulations.

**Storage Conditions:** Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Materials: Strong acids, strong bases, strong oxidizers.

7.3. Specific End Use(s)

Engine Oil .

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government.

Paraffin oils (8012-95-1)		
USA ACGIH	ACGIH TWA (mg/m³)	5 mg/m <sup>3</sup> (excluding metal working fluids, highly & severely refined-inhalable fraction)
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen highly and severely
		refined, Suspected Human Carcinogen highly and severely
		refined
USA OSHA	OSHA PEL (TWA) (mg/m³)	5 mg/m³
USA NIOSH	NIOSH REL (TWA) (mg/m³)	5 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (STEL) (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
USA IDLH	US IDLH (mg/m <sup>3</sup> )	2500 mg/m <sup>3</sup>
Alberta	OEL STEL (mg/m³)	10 mg/m <sup>3</sup>
Alberta	OEL TWA (mg/m³)	5 mg/m <sup>3</sup>
British Columbia	OEL TWA (mg/m³)	0.2 mg/m <sup>3</sup> (mildly refined)
		1 mg/m <sup>3</sup> (severely refined)
Manitoba	OEL TWA (mg/m³)	5 mg/m <sup>3</sup> (excluding metal working fluids, highly & severely
		refined-inhalable fraction)
New Brunswick	OEL STEL (mg/m³)	10 mg/m <sup>3</sup>
New Brunswick	OEL TWA (mg/m³)	5 mg/m <sup>3</sup> (as sampled by a method that does not collect
		vapor)
Newfoundland & Labrador	OEL TWA (mg/m³)	5 mg/m <sup>3</sup> (excluding metal working fluids, highly & severely
		refined-inhalable fraction)
Nova Scotia	OEL TWA (mg/m³)	5 mg/m <sup>3</sup> (excluding metal working fluids, highly & severely refined-inhalable fraction)
Nunavut	OEL STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Nunavut	OEL TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
Northwest Territories	OEL STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Northwest Territories	OEL TWA (mg/m³)	5 mg/m <sup>3</sup>
Ontario	OEL TWA (mg/m³)	5 mg/m <sup>3</sup> (pure, highly and severely refined, excluding
		metal working fluids-inhalable)
Prince Edward Island	OEL TWA (mg/m³)	5 mg/m <sup>3</sup> (excluding metal working fluids, highly & severely
		refined-inhalable fraction)
Québec	VECD (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (mist)
Québec	VEMP (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (mist)
Saskatchewan	OEL STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Saskatchewan	OEL TWA (mg/m³)	5 mg/m <sup>3</sup>
Yukon	OEL STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>

## line the second second

### Safety Data Sheet

 Yukon
 OEL TWA (mg/m³)
 5 mg/m³

### 8.2. Exposure Controls

**Appropriate Engineering Controls:** Ensure adequate ventilation, especially in confined areas. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national/local regulations are observed.

Personal Protective Equipment: Protective goggles. Gloves. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical goggles or safety glasses.

Skin and Body Protection: Wear suitable protective clothing.

**Respiratory Protection:** Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.

**Environmental Exposure Controls:** Do not allow the product to be released into the environment.

Consumer Exposure Controls: Do not eat, drink or smoke during use.

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on Basic Physical and Chemical Properties

		•
Physical State	:	Liquid
Appearance	:	Amber
Odor	:	Slight Hydrocarbon
Odor Threshold	:	Not available
рН	:	Not available
Evaporation Rate	:	Not available
Melting Point	:	Not available
Boiling Point	:	> 291 °C (555 °F)
Flash Point	:	> 204 °C (COC) (400 °F)
Auto-ignition Temperature	:	> 320 °C (COC) (608 °F)
Decomposition Temperature	:	Not available
Flammability (solid, gas)	:	Not available
Lower Flammable Limit	:	Not available
Upper Flammable Limit	:	Not available
Vapor Pressure	:	Not available
Relative Vapor Density at 20 °C	:	Not available
Relative Density	:	Not available
Specific Gravity	:	0.85
Solubility	:	Negligible
Partition Coefficient: N-Octanol/Water	:	Not available
Viscosity	:	Not available
Viscosity, Kinematic	:	Not available
Explosive Properties	:	Product is not explosive
Explosion Data – Sensitivity to Mechanical Impact	:	Not expected to present an explosion hazard due to mechanical impact

**Image: Construction States of Construction Construction** 

### Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

**Explosion Data – Sensitivity to Static Discharge** : Not expected to present an explosion hazard due to static discharge

### SECTION 10: STABILITY AND REACTIVITY

**10.1. Reactivity:** Hazardous reactions will not occur under normal conditions.

10.2. Chemical Stability: Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

**10.4. Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible materials, and other ignition sources.

10.5. Incompatible Materials: Strong acids, strong bases, strong oxidizers.

**10.6.** Hazardous Decomposition Products: Thermal decomposition generates: carbon oxides (CO, CO<sub>2</sub>). Hydrocarbons.

### SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on Toxicological Effects - Product

Acute Toxicity: Not classified

LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Not classified

**Eye Damage/Irritation:** Not classified

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not classified

Carcinogenicity: Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Overexposure may be irritating to the respiratory system.

Symptoms/Injuries After Skin Contact: Repeated or prolonged skin contact may cause irritation.

Symptoms/Injuries After Eye Contact: Direct contact with the eyes is likely irritating.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: Not Classified

### 11.2. Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Paraffin oils (8012-95-1)		
LC50 Inhalation Rat	2062 ppm/4h	
ATE US (gases)	2,062.00 ppmV/4h	
Heavy paraffinic, Distillates, petroleum, hydrotreated heavy paraffinic (64742-54-7)		
LD50 Oral Rat	> 2000 mg/kg	
LD50 Dermal Rabbit	> 2 g/kg	
Petroleum distillates, solvent dewaxed (64742-65-0)		
LD50 Oral Rat	> 5000 mg/kg	
LD50 Dermal Rabbit	> 5 g/kg	
Paraffin oils (8012-95-1)		
IARC Group	1	

### SECTION 12: ECOLOGICAL INFORMATION

### Safety Data Sheet

PURAMAX CleanFleet HDEO (All Grades) SDS# 5041, Version 1.0 Effective Date 6/1/2015 According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

### 12.1. Toxicity

Ecology - General: Toxic to aquatic life.

Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (68649-42-3)		
LC50 Fish 1	1.0 - 5.0 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])	
EC50 Daphnia 1	1 - 1.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
LC 50 Fish 2	10.0 - 35.0 mg/l (Exposure time: 96 h - Species: Pimephales promelas [semi-static])	
Petroleum distillates, solvent dewaxed (64742-65-0)		
EC50 Daphina 1	> 1000 mg/L (Exposure time: 48 h – Species: Daphnia magna)	
LC50 Fish 1	> 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)	
Distillates, petroleum, hydrotreated heavy paraffinic (64742-54-7)		
LC50 Fish 1	> 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)	
EC50 Daphnia 1	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)	

### 12.2. Persistence and Degradability

Not available

### 12.3. Bioaccumulative Potential

Not available

12.4. Mobility in Soil

Not available

### 12.5. Other Adverse Effects

Other Information: Avoid release to the environment.

### SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

Sewage Disposal Recommendations: Do not empty into drains; dispose of this material and its container in a safe way. Do not empty into drains. Do not dispose of waste into sewer.

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

### SECTION 14: TRANSPORT INFORMATION

- 14.1. In Accordance with DOT
  14.2. In Accordance with IMDG
  14.3. In Accordance with IATA
  14.4. In Accordance with IATA
  14.4. In Accordance with TDC
  14.5. Not regulated for transport
  14.6. Not regulated for transport
- **14.4.** In Accordance with TDG Not regulated for transport

SECTION 15: REGULATORY INFORMATION	
15.1. US Federal Regulations	
SARA Section 311/312 Hazard Classes	Not Classified

### 15.2. US State Regulations

### Paraffin oils (8012-95-1)

U.S. - California - Right To Know List – Warning: This material may contain chemicals known to the State of California to cause cancer, birth defects or other reproductive harm, and which may be subject to the warning requirements of California Proposition 65 (CA Health & Safety Code Section 25249.5)

U.S. - Massachusetts - Right To Know List

## Safety Data Sheet

PURAMAX CleanFleet HDEO (All Grades) SDS# 5041, Version 1.0 Effective Date 6/1/2015

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

### U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

### 15.3. Canadian Regulations

WHMIS Classification	Not Classified		
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (68649-42-3)			
Listed on the Canadian DSL (D	omestic Substances List)		
WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects		
Paraffin oils (8012-95-1)			
Listed on the Canadian DSL (D	omestic Substances List)		
Listed on the Canadian IDL (In	gredient Disclosure List)		
IDL Concentration 1 %			
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects		
Petroleum distillates, solver	it dewaxed (64742-65-0)		
Listed on the Canadian DSL (D	omestic Substances List)		
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria		
Distillates, petroleum, hydrotreated heavy paraffinic (64742-54-7)			
Listed on the Canadian DSL (D	Listed on the Canadian DSL (Domestic Substances List)		
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria		
This was durated as here a large if:			

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

### SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date	: 05/16/2015
Other Information	: This document has been prepared in accordance with the SDS requirements of the OSHA
	Hazard Communication Standard 29 CFR 1910.1200.
GHS Full Text Phrases:	

P273	Avoid release into the environment
P501	Dispose of contents/container in accordance with local, regional, national, and international
	regulations.

### Party Responsible for the Preparation of This Document

North American Lubricants Company 7337 E. Doubletree Ranch Road, Suite 180 Scottsdale, AZ 85258 (800)430-6252 www.nalube.com

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

North America GHS US 2012 & WHMIS 2