(a) NORTH AMERICAN LUBRICANTS

PURAMAX Fleet HDMO (All Grades)

SDS# 5042, Version 1.0 Effective Date 9/3/2020

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Safety Data Sheet

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Name: PURAMA

Product Name: PURAMAX Fleet

Product Grades/Codes:

PURAMAX Fleet SAE 10 - 2111303221 (Tote) PURAMAX Fleet SAE 30 - 2111343221 (Tote)

Synonyms: Heavy Duty Engine Oil

1.2. Intended Use of the Product

Heavy Duty Engine Oil.

1.3. Company Identification

North American Lubricants Company 7337 E. Doubletree Ranch Road, Suite 180 Scottsdale, AZ 85258 (800)430-6252 www.nalube.com

1.4. Emergency Telephone Number

Emergency Number : CHEMTREC: (800)424-9300 or (703)527-3887

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

Classification (GHS-US)

Not Classified

Full text of H-phrases: see section 16

2.2. Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US) : No known significant effects or critical hazards

Signal Word (GHS-US) : No signal word

Hazard Statements (GHS-US) : No known significant effects or critical hazards

Precautionary Statements (GHS-US) : No precautionary phrases

2.3. Other Hazards

The mixture consists of substances capable of producing an aspiration hazard. Aspiration may result in chemical pneumonia (fluid in the lungs), severe lung damage, respiratory failure, and even death.



SDS# 5042, Version 1.0 Effective Date 9/3/2020

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Safety Data Sheet

2.4. Unknown Acute Toxicity (GHS-US)

20.73 percent of the mixture consists of ingredient(s) of unknown acute toxicity.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Not applicable

3.2. Mixture

Name	% (w/w)
Single HDMO, SAE 10W, 30	100
Refined and hydrotreated light distillate mineral oil	60-70
Refined and hydro processed heavy distallate/residual mineral base oil	25-50
Additive system containing proprietary formulated ingredients	3-8
Other minor additives	<1

^{*}The specific chemical identity and/or exact percentage of composition have been withheld as a trade secret within the meaning of the OSHA Hazard Communication Standard [29 CFR 1910.1200].

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible). **Inhalation:** Remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.

Skin Contact: Remove contaminated clothing. Drench affected area with water or soap and water for at least 15 minutes. Wash contaminated clothing before reuse. Obtain medical attention if irritation develops or persists.

Eye Contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

Ingestion: Do NOT induce vomiting. Rinse mouth. Immediately call a POISON CENTER or doctor/physician.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

General: No known significant effects or critical hazards.

Inhalation: Overexposure may be irritating to the respiratory system. **Skin Contact:** Repeated or prolonged skin contact may cause irritation.

Eye Contact: Direct contact with the eyes is likely irritating.

Ingestion: Ingestion is likely to be harmful or have adverse effects. **Chronic Symptoms:** No known significant effects or critical hazards.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If you feel unwell, seek medical advice (show the label where possible).

^{*}More than one of the ranges of concentration prescribed by Controlled Products Regulations has been used where necessary, due to varying composition.

SDS# 5042, Version 1.0 Effective Date 9/3/2020

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Safety Data Sheet

SECTION 5: FIRE-FIGHTING MEASURES

5.1. NFPA RATING

HEALTH 1 | FLAMMABILITY 1 | REACTIVITY 0 | SPECIAL --

5.2. Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.3. Special Hazards Arising from the Substance or Mixture

Fire Hazard: Not flammable but will support combustion.

Explosion Hazard: Product is not explosive.

Reactivity: Hazardous reactions will not occur under normal conditions.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire. Under fire conditions, hazardous fumes will be present.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection. **Hazardous Combustion Products:** Under fire conditions, may produce fumes, smoke, oxides of carbon and hydrocarbons.

Other Information: Refer to Section 9 for flammability properties.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid all contact with skin, eyes, or clothing. Avoid breathing (vapor, mist, spray).

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Stop leak if safe to do so. Eliminate ignition sources. Ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. **Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely. Spills should be contained with mechanical barriers. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Heading 8. Exposure controls and personal protection. For further information refer to section 13.

SDS# 5042, Version 1.0

Effective Date 9/3/2020

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Safety Data Sheet

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: Any proposed use of this product in elevated-temperature processes should be thoroughly evaluated to assure that safe operating conditions are established and maintained. Practice good housekeeping - spillage can be slippery on smooth surface either wet or dry.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep/Store away from

direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Materials: Strong acids, strong bases, strong oxidizers.

7.3. Specific End Use(s)

Heavy Duty Engine Oil

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government.

	OSHA 71		AC	GIH		OTHER
Standards ->	PEL/TWA	PEL/Ceiling	TLV/TWA	TLV/STEL		
Oil Mist ->	5 Mg/M ^{3*}	None	5 Mg/M ^{3*}	10 Mg/M ^{3*}	None	(*Oil Mist, Mineral

8.2. Exposure Controls

Appropriate Engineering Controls: Ensure adequate ventilation, especially in confined areas. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national/local regulations are observed.

Personal Protective Equipment: Protective goggles. Gloves. Insufficient ventilation: wear respiratory protection.







Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical goggles or safety glasses.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed

established Occupational Exposure Limits.

Environmental Exposure Controls: Do not allow the product to be released into the environment.

Consumer Exposure Controls: Do not eat, drink or smoke during use.

MORTH AMERICAN LUBRICANTS

PURAMAX Fleet HDMO (All Grades)

SDS# 5042, Version 1.0

Effective Date 9/3/2020

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State: LiquidBoiling Point: N/AEvaporation Rate: N/ASolubility in Water: NegligiblePH: N/A

Auto Ignition Temperature : >320°C/608°F

Gravity (H2O=10.0) API @ 60°F : 27.9 – 24.9

Percent Volatile by Volume : Negligible

Vapor Pressure: < 0.3kPa (0.1 @ 20°C [Est])</th>Upper/Lower Explosion/ Flammability Limits: 1-10 % V (based on Mineral Oil)Melt Point: N/A Pour Point: -25°F to 5°F

Vapor Density : (Air = 1.0) > 1.0Odor : Mild Hydrocarbon

Electrical Conductivity : Not expected to be static accumulator

Flash Pt. COC : 400°F to 465°F Viscosity @ 100°C, cSt : 6.5 – 18.7 Viscosity @ 40°C, cSt : 42 - 233

SECTION 10: STABILITY AND REACTIVITY

- **10.1. Reactivity:** Hazardous reactions will not occur under normal conditions.
- 10.2. Chemical Stability: Stable under recommended handling and storage conditions (see section 7).
- **10.3.** Possibility of Hazardous Reactions: Hazardous polymerization will not occur.
- **10.4. Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible materials, and other ignition sources.
- **10.5. Incompatible Materials:** Strong acids, strong bases, strong oxidizers.
- **10.6.** Hazardous Decomposition Products: Thermal decomposition generates: carbon oxides (CO, CO₂). Hydrocarbons.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects - Product

Acute Toxicity: Not classified LD50 and LC50 Data: Not available Skin Corrosion/Irritation: Not classified Eye Damage/Irritation: Not classified

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not classified **Carcinogenicity:** Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified



SDS# 5042, Version 1.0 Effective Date 9/3/2020

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Safety Data Sheet

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Overexposure may be irritating to the respiratory system. **Symptoms/Injuries After Skin Contact:** Repeated or prolonged skin contact may cause irritation.

Symptoms/Injuries After Eye Contact: Direct contact with the eyes is likely irritating.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: Not Classified

11.2. Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Dermal LD50	>5. g/kg (Rabbit)	OSHA – Non-Toxic	Based on similar materials(s)	
Oral LD50	>5. g/kg (Rat)	OSHA – Non-Toxic	Based on similar materials(s)	
Carcinogenicity Classification (Highly Refined Mineral Oil/IP346<3%)			IARC 3=No carcinogenicity to humans	ACGIH A4 = Unclassified as a IOSHA= NO
Human Carcinogen	GHS/CLP=No carcinogenicity classification		NTP = No	

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General: Toxic to aquatic life.

12.2. Persistence and Degradability

Not available

12.3. Bio accumulative Potential

Not available

12.4. Mobility in Soil

Not available

12.5. Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Sewage Disposal Recommendations: Do not empty into drains; dispose of this material and its container in a safe way. Do not empty into drains. Do not dispose of waste into sewer.

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.



SDS# 5042, Version 1.0 Effective Date 9/3/2020

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Safety Data Sheet

SECTION 14: TRANSPORT INFORMATION

14.1. In Accordance with DOT
 14.2. In Accordance with IMDG
 14.3. In Accordance with IATA
 14.4. In Accordance with TDG
 Not regulated for transport
 Not regulated for transport
 Not regulated for transport

SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

U.S. TSCA 8b INVENTORY:	All components of this product are on the US TSCA Inventory.
Other TSCA Regulations:	None Known.
SARA SECTIONS 301 – 304	This product does not contain greater than 1.0% of any chemical substance on the SARA
	Extremely Hazardous Substances List.
SARA SECTION 311/312 (Hazard):	This product does not contain any chemical substance on SARA Hazard, Delayed Health
	Hazard List.
SARA SECTION 313:	This product does not contain greater than 1.0% (greater than 0.1% for carcinogenic
	substance) of any chemical (Toxic Chemicals) substances listed under SARA Section 313.
CERCLA HAZARDOUS SUBSTANCES:	None Known.
FDA APPROVAL:	Not Applicable
RCRA STATUS:	If discarded in its purchased form, this product would not be a hazardous waste either by
	listing or by characteristic. Under RCRA it is the responsibility of the product user to
	determine at the time of disposal, whether a material containing the product or derived from
	the product should be classified as a hazardous waste.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date : 09/03/2020

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA

Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

P273	Avoid release into the environment
P501	Dispose of contents/container in accordance with local, regional, national, and international regulations.

Party Responsible for the Preparation of This Document

North American Lubricants Company 7337 E. Doubletree Ranch Road, Suite 180 Scottsdale, AZ 85258 (800)430-6252 www.nalube.com

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. North American Lubricants Company assumes no responsibility for injury from the use of the product described herein.

North America GHS US 2012 & WHMIS 2