



PURATECH Supreme Motor Oil

PURATECH Supreme Motor Oil is an API SN premium engine oil designed to provide superior performance in both passenger cars and light trucks. PURATECH Supreme Motor Oil in SAE grades 10W-40 and 20W-50 are licensed by API for Service Category SN and are backwards compatible to all earlier API categories.

PURATECH Supreme Motor Oil is formulated with state-of-the-art additive technology and high-quality base oil to offer ultimate engine protection. Additionally, PURATECH Supreme Motor Oils contain dispersant additives specially developed to provide superior rust, corrosion and oxidation protection. PURATECH Supreme Motor Oil is also formulated with an antifoam agent to prevent excessive foaming during severe engine operation.

APPLICATIONS

PURATECH Supreme Motor Oils are recommended for gasoline engines used in passenger cars, light trucks, sports-utility vehicles, powerboats, and additional applications where an SAE 10W-40 or 20W-50 oil is specified.

FEATURES AND BENEFITS

- Superior wear protection
- Protection from varnish deposits and sludge caused by stop-and-go driving
- Resistance to viscosity and high-temperature thermal breakdown
- Improved fuel economy
- Excellent low-temperature pumpability for cold starts

RECOMMENDED PERFORMANCE SPECIFICATIONS

- API Resource Conserving SN and all previous "S" categories

PURATECH Supreme Motor Oil		Typical Characteristics	
	<i>Test Method</i>	<i>SAE Viscosity Grade</i>	
		<i>10W-40</i>	<i>20W-50</i>
Gravity, °API	1298	31.5	30
Flash Point, COC °C/°F	92	220/428	230/446
Pour Point, °C/°F	97	-24/-11	-24/-11
Viscosity			
cSt @ 40 °C	445	97.0	160
cSt @ 100 °C	445	13.8	18.5
Viscosity Index	2270	145	130
CCS Viscosity (mPa.s)	5298	<7000@-25	<7500@-15

Minor variations in test data are to be expected in normal manufacturing