

PureSYN AMT 75W-90 GL-4

PureSYN AMT 75W-90 is a synthetic heavy-duty transmission fluid specifically formulated for Daimler DT-12 Automated Manual Transmissions (AMT) installed on most Freightliner or Western Star trucks that have DD15 or DD13 diesel engines. This premium fluid is engineered for extended drain intervals up to 300,000 miles.

High viscosity index base oils and advanced additive chemistry provide outstanding thermal and oxidation stability, extreme pressure protection and excellent resistance to rust and corrosion.

APPLICATIONS

Recommended for use in Daimler DT-12 automated manual transmissions. Also recommended for use in applications calling for an API GL-4 and SAE 75W-90 viscosity grade.

FEATURES AND BENEFITS

- · 300,000-mile extended drain intervals
- Improved fuel efficiency
- Excellent Oxidation resistance
- Enhanced extreme temperature performance
- Improved component protection
- · Promotes long equipment life

RECOMMENDED PERFORMANCE SPECIFICATIONS

- API Service Category GL-4
- Daimler MB 235.11 (Not Officially Approved by Mercedes Benz)
- MAN 341 Type MB
- ZF TE-ML 08

PureSYN AMT 75W-90 GL-4		Typical Characteristics
	Test Method ASTM -D	SAE Viscosity Grade
		75W-90
API Classification		GL-4
Brookfield Viscosity, cP @ -40°C	2983	53,000
Viscosity		
cSt @ 40°C	445	87.39
cSt @ 100°C	445	14.4
Viscosity Index	2270	173
Flash Point, °C/°F	92	208/406
Pour Point, °C/°F	97	-42/-44

Minor variations in test data are to be expected in normal manufacturing